TWIN CITY HOSE, INC.

U LOOP GROOVE END 2"



MATERIALS

#1-2 HOSE & BRAID: STAINLESS STEEL HOSE WITH 1-LAYER OF STAINLESS STEEL BRAID

#3 BRAID BAND: STAINLESS STEEL

#4 END FITTING: SCH. 40 CARBON STEEL GROOVE

#5 ELBOWS: SCH. 40 CARBON STEEL

#6 HANGER *12" ID AND LARGER ARE SCHEDULE STANDARD (STD)

#7 PORT (OPTIONAL): ☐

QTY	MODEL #	SIZE	"A" DIM.	"B" DIM.	WRK. PSIG	MAX TEST	@ TEMP.	LATERAL OFFSET	WT. LBS.
	SL200762	2"	19 ½"	22 ½"	370	555	70°F	2"	13
	SL250762	2 ½"	21 ¾"	23"	400	600	70°F	2"	22
	SL300762	3"	24"	25 ¾"	288	431	70°F	2"	30
	SL400762	4"	30"	31"	250	375	70°F	2"	51
	SL500762	5"	36"	38"	200	300	70°F	2"	82
	SL600762	6"	42"	41 ½"	220	330	70°F	2"	126
	SL800762	8"	56"	53 ¼"	215	323	70°F	2"	254
	SL010762	10"	68"	61 ¾"	200	350	70°F	2"	429
	SL012762	*12"	80"	71"	160	240	70°F	2"	619

TEMPERATURE DERATING FACTORS: MULTIPLY X WRK. PSIG									
200° F	250° F	300° F	350° F	400° F	500° F	600° F	700° F	800° F	900° F
0.94	0.92	0.88	0.86	0.83	0.78	0.74	0.7	0.66	0.62

DRAWN BY: _____ **DRAWING NUMBER:** _____ **REV:** _____

SIGNATURE: _____ **DATE:** _____

PO NUMBER: _____ **PROJECT:** _____

CUSTOMER: _____ **NOTES:** ☐

20615 Commerce Blvd., Rogers, MN 55374 P 1-800-670-9475 F 763-428-5111 E sales@twincityhose.com W www.twincityhose.com