


### V90 MMT 4"



**MATERIALS**

- #1-2 HOSE & BRAID: STAINLESS STEEL HOSE WITH 1-LAYER OF STAINLESS STEEL BRAID
- #3 BRAID COLLAR: STAINLESS STEEL
- #4 END FITTINGS: SCH. 40 CARBON STEEL MALE NPT
- #5 ELBOWS: SCH. 40 CARBON STEEL
- #6 HANGER
- #7 PORT (OPTIONAL):

QTY	MODEL NUMBER	SIZE	OAL DIM.	"H" DIM.	WRK. PSIG	MAX TEST	MOTION X,Y,Z	WT. LBS.
	SV050014	1/2"	28"	10"	1100	1650	4"	2
	SV075014	3/4"	30"	11 1/2"	597	895	4"	3
	SV100014	1"	33"	12 3/4"	580	870	4"	5
	SV125014	1 1/4"	36 3/4"	14 1/2"	441	661	4"	7
	SV150014	1 1/2"	40 1/2"	16"	370	555	4"	9
	SV200014	2"	45 1/4"	18 1/4"	370	555	4"	15
	SV250014	2 1/2"	44 3/4"	17 1/2"	400	600	4"	25
	SV300014	3"	49"	19 1/4"	288	431	4"	30

TEMPERATURE DERATING FACTORS: MULTIPLY X WRK. PSIG									
200° F	250° F	300° F	350° F	400° F	500° F	600° F	700° F	800° F	900° F
0.94	0.92	0.88	0.86	0.83	0.78	0.74	0.7	0.66	0.62

DRAWN BY:

DRAWING NUMBER:

REV:

SIGNATURE:

DATE:

PO NUMBER:

PROJECT:

CUSTOMER:

NOTES: