




UL CLASSIFIED MH59973
UL SS V90 MMT 3"



MATERIALS

#1-2 HOSE & BRAID: T-321 STAINLESS STEEL CORRUGATED HOSE WITH 1-LAYER OF T-304 STAINLESS STEEL BRAID

#3 BRAID COLLAR: T-304 STAINLESS STEEL

7 DRAIN PORT (OPTIONAL):

#4 END FITTING: STAINLESS STEEL MALE NPT

#5 ELBOWS: STAINLESS STEEL

#6 HANGER

QTY	MODEL NUMBER	SIZE	OAL DIM.	"H" DIM.	WRK. PSIG	MAX TEST	MOTION X,Y,Z	WT. LBS.
	UL-SV050033	1/2"	25 3/4"	9"	1100	1650	3"	2
	UL-SV075033	3/4"	26 3/4"	10"	800	1200	3"	3
	UL-SV100033	1"	29 3/4"	11"	750	1125	3"	5
	UL-SV125033	1 1/4"	34 3/4"	13 1/4"	725	1088	3"	7
	UL-SV150033	1 1/2"	36 3/4"	14"	565	850	3"	9
	UL-SV200033	2"	39 3/4"	15 1/4"	500	750	3"	15
	UL-SV250033	2 1/2"	42 1/2"	16 1/4"	400	600	3"	25
	UL-SV300033	3"	46 1/2"	18"	288	431	3"	30

TEMPERATURE DERATING FACTORS: MULTIPLY X WRK. PSIG							
200° F	250° F	300° F	350° F	400° F	500° F	600° F	700° F
0.94	0.92	0.88	0.86	0.83	0.78	0.74	0.7

DRAWN BY:

DRAWING NUMBER:

REV:

SIGNATURE:

DATE:

PO NUMBER:

PROJECT:

CUSTOMER:

NOTES: